



K 130

TWO WAY SYSTEM


220 W

T 24.3 - Tweeter:


1. 24mm diaphragm Neodymium tweeter with PEI dome, for a brilliant reproduction of high frequencies in a compact size.
2. Annular acoustic lens optimized for exceptional off-axis performance.
3. 6dB/Oct crossover integrated on tweeter wiring.
4. Mounting accessories for external or embedded mounting included.

V 130.3 - Woofer:

1. V-cone® design for best off-axis response, clear mid-high frequency detail and powerful bass.
2. Foam surround combining high sensitivity and deep bass response.
3. Pure copper 25 mm (1 in.) voice coil woofer for high dynamic power handling.
4. High flux density 70 mm (2.76 in.) ferrite magnet for a powerful undistorted sound.
5. Easy-to-install DIN size basket protected by abrasion-resistant dust paint.



A	130 mm	5.12 in.
B	116 mm	4.57 in.
C	59 mm	2.32 in.
D	52 mm	2.05 in.



A	34 mm	1.3 in.
C	20 mm	0.8 in.
D	13 mm	0.5 in.

TECHNICAL SPECIFICATIONS

Component		2-way system
Size		
Woofer	mm (in.)	130 (5)
Tweeter diaphragm	mm (in.)	24 (0.9)
Voice Coil Ø		
Woofer	mm (in.)	25 (1)
Tweeter	mm (in.)	14 (0.55)
Power Handling	W peak	220
	W continuous	55
Sensitivity	dB SPL	93
Impedance	Ω	4
Frequency Response	Hz	55 ÷ 23k
Crossover	6 dB/Oct tweeter integrated	
Weight of one component		
Woofer	kg (lb)	0,53 (1.17)
Tweeter	kg (lb)	0,03 (0.07)
Woofer Magnet	High density flux ferrite	
Tweeter Magnet	Neodymium	
Cone	Water-repellent pressed paper	
Dome	PEI	
Xmech	mm (in.)	±3,5 (0.14)